

DESCRIPTION

Skim coat for interiors with decorative and filling function. Adheres to various materials and is distinguished by good workability.
 Paste composed of specially designed fillers and binders which make the product extremely hard and fast drying. This composition guarantees easy skimming, sandpapering and polishing. Thanks to these features, the filler *Décor Stucco* is excellent for obtaining a "Venetian style" coating.

PROPERTY OF THE PRODUCT

Adhesion	GOOD	Method
Drying time	Time for excellent resistance to washing	interior PF16
	5 days	interior PF2
Solid by weight	80-84 %	interior PF25

SPECIFICATION DATA

Drying time	fully 24h	Method
		interior PF2

SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

COLOUR RANGE

White.

TYPICAL USE

Surfaces of various kinds such as plaster, gypsum, wood.

TOOLS

Stainless steel trowel, stainless steel spatula.

THINNING

Ready to use.

COVERAGE

0.9-1.1 m²/kg

APPLY

+5°C +30°C

COATING SYSTEM

1. One or more skims are applied with the aid of a stainless steel trowel, until, after sandpapering with abrasive paper, a totally smooth surface is obtained.
2. Following this smoothing process, which normally takes place after approx. 12 hours of drying, the wall is "dabbed" with the product using a spatula for filler approx. 8 cm wide. The "dab marks" are made leaving empty spaces which will be filled in later, in 3 or 4 consecutive time intervals, in order to allow the "dab marks" made earlier to dry out.
3. After having filled the entire wall and obtained a typical fish scale pattern, the next stage involves "polishing" with a spatula or stainless steel trowel.

In applications on substrates other than smooth plaster, the substrate should be appropriately treated. If the substrate is made of gypsum, it should be insulated with Acrilifix, and if it is made of wood, with *Opakite*. On smooth surfaces (plasterboard, old coats of smooth paint), before proceeding with the work using the Decorstucco, apply *Unifix undercoat* diluted 20-30% by weight with water. Tools should be washed with water immediately after use.

SPECIFICATION ITEM

Skim coat for interiors with decorative and filling function, "Venetian stucco" style, dry polishable, to be applied in successive skim coats with marks using an 8 cm spatula at an average consumption rate of 1 kg/m².

INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In

different conditions the data and the time intervals between the two phases of the above reported coating system can vary.