

## PRODUCT DATA SHEET

# FIBER FINITURA

Opaque dimming effect finish

## DESCRIPTION

Water-based paint, waterproof and moderately breathable, easy to apply. Ideal for interiors, opaque, odourless, semi-covering, formulated with acrylic resins in water-based emulsion, ideal for creating special decorations with a fibre effect, soft and textured to the touch.

Being odorless, it is particularly indicated for applications in poorly ventilated areas. It is made with raw materials chosen for a low impact, with reduced pollution and with minimal emissions in order to preserve the wellbeing and safety of users and people living in the environment.

## PRODUCT PROPERTY

	Value	Method
<b>Water vapour permeability</b>	GOOD	
<b>Impact resistance</b>	EXCELLENT	
<b>Direction of dirt</b>	LOW	
<b>Washing resistance (after 5gg)</b>	EXCELLENT	
<b>Solid by weight</b>	34-38 %	Internal PF25

## SPECIFICATION DATA

	Value	Method
<b>SPECIFIC WEIGHT</b>	960-1060 g/l	Internal PF3
<b>DRYING</b>	Overcoatable 5-8h; Full 5 days.	Internal PF2

## SHELF LIFE

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

## COLOUR RANGE

As per samples.

The colour could vary slightly from one production batch to the next; it is therefore important to finish the job with the same batch.

## TYPICAL USE

It is ideal as a finish for creating an impressive decorative effect in both in public and private surroundings, where special decorations are required. The substrates used must be skimmed and absolutely smooth.

The texture effect depends on the manual skill of the applicator and on the quantity applied. For this reason the samples are only indicative. Before doing the job, run some tests using a demonstration panel. In order to obtain an even surface, work with the same tool and one applicator only in the finishing phase, and ensure continuous wet-on-wet covering of the entire wall without interruption.

Tools should be washed with water immediately after use.

## TOOLS

Roller, Brush Spalter- Brush, Sponge.

## THINNING

10-15% with water

## COVERAGE

15-18 m<sup>2</sup>/l per coat.

## APPLY

+5°C +30°C

## COATING SYSTEM

On concrete, various plasters, new or already painted, rough and irregular, clean the surface to be decorated by removing any parts that are detached and skim with *Jolli* or *Stuccocap*.

On wood, apply Opakite primer o Opakite W and sandpaper.

On iron substrates, apply a coat of Chromocap or or Chromocap W.

Chromocap can be replaced by Antitruggine, Corrobloc, Primer Cap Universale

### On substrates prepared as described above and on plasterboard

1. Apply Fiber Fondo, ready to use, with a roller or a brush on wet paint and use the suggested tool for the desired finish.

## PRODUCT DATA SHEET

# FIBER FINITURA

Opaque dimming effect finish

2. After 8 hours, apply Fiber Finitura or any other decorative of Generation Art line (as Gem, Mineral, Pearl, etc.).

Apply DECOR PROTECTIVE to increase the resistance to abrasion, scratch and washing with detergents and edible liquid.

## SPECIFICATION ITEM

Semi-transparent paint for interiors, based on acrylic resins in aqueous emulsion, to apply on several supports or old paintings, pre-emptively treated with Fiber Fondo, with an average consumption of 55 ml/m<sup>2</sup> in a single layer.

## INSTRUCTIONS

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.