

**DESCRIPTION**

Powdered filler for interior use, composed of a mixture of plaster, alabaster, kaolin and special glues which give the product greater adhesion without cracking and a very long hardening time.

**PRODUCT PROPERTY**

ADHESION ON DIFFERENT SUBSTRATES	<b>Value</b> GOOD	<b>Method</b>
RESISTANCE TO CRACKING	GOOD	
POT LIFE	Minimum 90 min	

**SPECIFICATION DATA**

SOLID BY WEIGHT	100%	Internal PF25
APPEARANCE	<b>Value</b> POWDER	<b>Method</b>
ODOUR	ODOURLESS	

**SHELF LIFE**

1 year minimum, stored in its unopened original can at temperatures between +5°C and +30°C.

**COLOUR RANGE**

White.

**TYPICAL USE**

Skims coat, stopping-up of plasterboard, wood and similar, application of plaster cornices.

**TOOLS**

Spatula or Steel trowel.

**THINNING**

Mix with water until a smooth paste is obtained.

**APPLY**

+5°C +30°C

**SPECIFICATION ITEM**

Wall paste filler suitable for filling holes and cracks on interior walls, on different types of surfaces such as plaster, concrete, plasterboard wood in large thickness up to 2 cm with only one pass without any risk of cracking.

**INSTRUCTIONS**

To carry out the work in a proper way, it is needed to strictly follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.