

LAND

Textured metallic effect finish

DESCRIPTION

Waterbased paint, impermeable to water and adequately transpiring, easily applicable, ideal for professional use as it is highly compatible and features adhesion and workability on different types of substrate.

Suitable for interiors, opaque, odorless, semi-covering, formulated with acrylic resins in aqueous emulsion, and tenuously metallized pigments with rustic finish to create a changeable and pleasant play of light and reflected colors;

Idonea per interni, opaca, inodore, semicoprente, formulata con resine acriliche in emulsione acquosa, e pigmenti tenuamente metallizzati con finitura rustica così da creare un mutevole e gradevole gioco di luce e colori riflessi; suitable for obtaining special decorations with a rough and textured effect.

Its high quality ensures maximum protection with an excellent level of finish and provides a tough, elastic and tough film with high resistance to the penetration of stains and dirt. Allows easy cleaning even with common detergents.

Being odourless, it is particularly indicated for applications in poorly ventilated areas. It is made with raw materials chosen for a low impact, with reduced pollution and with minimal emissions in order to preserve the wellbeing and safety of users and people living in the environment; the product meets the requirements of the **Class A +** according to the relevant Test Report.

COMPOSITION

Paint based on acrylic resins in aqueous dispersion, selected inerts and perplexing pigments.

PRODUCT PROPERTY

	Value	Method
WATER VAPOUR DIFFUSION	Good	
IMPACT RESISTANCE	Excellent	
DIRT RETENTION	Low	
RESISTANCE TO WASHING (5 DAYS)	Excellent	
Solid by weight	Gold: 41-45% Silver: 40-44%	Internal PF25

SPECIFICATION DATA

	Value	Method
Specific weight	Silver: 1000-1100 g/l Gold: 1040-1140 g/l	Internal PF3
Drying time	Dry to recoat 5-8h; Fully 5 days;	Internal PF22

SHELF LIFE

1 year minimum, stored in its unopened and original can at temperatures between +5°C and +30°C.

COLOUR RANGE

As per samples.
The colour could slightly vary from one production batch to the next; it is therefore important to finish the job with the same batch.

TYPICAL USE

It is ideal for creating an impressive decorative effect in both public and private surroundings, where special decorations are required.

It is necessary to apply it on properly prepared surfaces.

The texture effect depends on the manual skill of the applicator and on the quantity applied. For this reason, the samples are only indicative. Before doing the job, run some tests using a demonstration panel.

To obtain a homogeneous surface, work with the same tool and with one operator in the finish, and ensure continuous wet-on-wet processing of the entire wall without interruptions. Mix the product 2 minutes before and after the introduction of colorants AC16 to the mixer.

The application of the single non-pigmented base can give rise to evident color differences, therefore the product must be applied only and exclusively after having pigmented it according to the relative color chart.

Tools to be washed with water immediately after use.

LAND

Textured metallic effect finish

TOOLS Spalter brush, Stiff short-hair brush.

THINNING Up to 10% by volume with water.

COVERAGE 9-12 m²/l per coat.

APPLY +5°C +30°C

COATING SYSTEM On various plasters, new or already painted, rough and irregular, clean the surface to be decorated by removing any parts flaking off and apply *Jolli* or *Stuccocap skim coat*. Filler.

On iron substrates, apply a coat of Chromocap or or Chromocap W.
Chromocap can be replaced by Antitruiggine, Corrobloc, Primer Cap Universale

On substrates prepared as described above and on plasterboard

1. Using a short-hair roller, apply a coat of *Ecolora Absolutecap* diluted 5-10% by volume with water.
2. After 3 hours, apply a coat of *Land* diluted by 5-10% with water using a brush, spreading the sand contained inside, in an irregular or circular manner.

Apply DECOR PROTECTIVE to increase the resistance to abrasion, scratch and washing with detergents and edible liquid.

SPECIFICATION ITEM

Acrylic painting for interiors, in aqueous dispersion, suitable for metallic textured effect finishes with high wash resistance, to apply in single layer, with an average consumption of 0.1 l/m² on skimmed and pre-emptively treated surface with a coat of *Ecolora Absolutecap*.

INSTRUCTIONS

To carry out the work in a proper way, it is strictly necessary to follow the instructions for the preparation of the surfaces contained in the CAP Arreghini Books. This technical information is intended as a rough guide. However, because of the enormous variety of media and application conditions, it is essential to check the suitability of the product and test the effectiveness on a sample. The specification data and technical information have been calculated at +23°C with relative ambient humidity of 65%. In different conditions the data and the time intervals between the two phases of the above reported coating system can vary.